

## DS-D4215FI-GW Full-Color LED Display Unit



### Features and Functions

#### Perfect dot-by-dot display without distortion

- Easily form a standard 1920 × 1080 screen, achieving high definition dot-by-dot display.
- Automatically adapt signal sources to screens without the help of a video processing equipment.

#### Complete interfaces

- HDMI, DVI, and DP inputs.
- Network interface output.
- Remote configuration via the debugging network interface.

#### High load capacity

A signal input of 4K resolution at 30 Hz, and an output of up to 4K resolution for a single device.

#### Image enhancement

- Unique 3-pixel technology enhances images three-dimensionally.
- Dynamically enhance image parameters such as contrast, sharpness, saturation, color temperature, and color gamut to get more vivid.

#### Easy to use

- Use the buttons on the panel of sending card to adjust brightness and switch signal.
- Use the remote controller to navigate through menu.
- Compatible with Hikvision tablet keyboards for remote operation.

#### Safe and reliable

- Automatically remove moisture to protect lamp boards from water damage when the device is kept in a humid environment or left unused for a long time.
- Back up signals to maintain a reliable system.



## Easy to install

- Three-axis XYZ structure is designed to perfectly adjust the smoothness of the entire screen.
- Rapidly eliminate bright and dim lines without the help of a dedicated device or operation.

## Specifications

<b>Model</b>	<b>DS-D4215FI-GW</b>
<b>Pixel Configuration</b>	Surface mounted trinity LED
<b>Encapsulation Brand</b>	NationStar gold wire
<b>Driver IC</b>	MBI5153
<b>Housing Included</b>	Yes
<b>Power Supply Brand</b>	Megmeet
<b>Control System</b>	Hikvision-developed
<b>Pixel Pitch</b>	1.588 mm
<b>Dimensions (W×H×D)</b>	609.92 × 343.08 × 75 mm (24.0 × 13.5 × 2.95 inch)
<b>Packing Dimensions (W×H×D)</b>	796 × 484 × 192 mm (31.33 × 19.05 × 7.56 inch)
<b>Resolution</b>	384 × 216
<b>Pixel Density</b>	396,384 pitch/ m <sup>2</sup>
<b>Area</b>	0.209 m <sup>2</sup>
<b>Aspect Ratio</b>	16:9
<b>Material</b>	Sealed die casting aluminum
<b>Maintenance Method</b>	Magnet front maintenance for lamp boards, and rear maintenance for power supply and receiving card
<b>Max. Brightness</b>	500 nits
<b>Brightness Control</b>	Manual/Automatic/Remote controller
<b>Color Temperature</b>	3000 to 10000 adjustable
<b>Viewing Angle</b>	Horizontal 160°, vertical 160°
<b>Optimal Viewing Distance</b>	6 m
<b>Center Distance Deviation of LED</b>	< 3%
<b>Brightness Uniformity</b>	≥ 97%
<b>Color Uniformity</b>	≤ ± 0.003Cx, Cy
<b>Contrast</b>	≥ 3000:1
<b>Driving Mode</b>	Constant current driving
<b>Frame frequency</b>	60 Hz
<b>Refresh Rate</b>	3840 Hz
<b>Power Supply</b>	100 to 240 VAC
<b>Max. Consumption</b>	≤ 850 W/m <sup>2</sup>
<b>Average Consumption</b>	< 280 W/m <sup>2</sup>
<b>Operating Temperature</b>	-10°C to 40°C (14°F to 104°F)
<b>Storage Temperature</b>	-20°C to 60°C (-4°F to 140°F)
<b>Operating Humidity</b>	10% to 80% (non-condensing)
<b>Storage Humidity</b>	10% to 85% (non-condensing)
<b>Gross Weight</b>	9.8 kg (21.6 lb including packaging)
<b>Wet Weight</b>	9.3 kg (20.5 lb)

\*: All specifications mentioned above are subject to the actual product.

## Recommended Accessory



DS-D42C04-H Sending Card

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com