



Portable Projector

Vivitek-DH3760Z

FullHD projector with a brilliant image, Simple I/O ports and long-life light source making it ideally suited for small & medium-sized meeting rooms



Features

- Up to 4,500 ISO lumens with strong contrast
- Native 1080P resolution with WUXGA support
- Lamp-free, filter-free laser design with up to long hours of use
- Low maintenance and reduced total cost of ownership
- Manual focus and optical zoom for flexible setup
- Versatile connectivity with dual HDMI, USB-A, audio out, and RS232
- Powerful built-in loudspeaker for bold, clear sound
- Intuitive multilingual on-screen display
- Automatic or manual horizontal and vertical keystone correction
- Energy-efficient standby mode at less than 0.5W
- Compact and lightweight at just 2.8 kg

Specifications

Display Type	Single Chip 0.65" DLP Technology by TI	
Brightness	4,500 Lumens*	
Native Resolution	1080P (1920 x 1080)	
Maximum Resolution	4K-UHD (4096 x 2160)	
Contrast Ratio	3,000,000:1(Dynamic Contrast Ratio)	
Laser Life/Type	20,000 / 30,000 hours (Normal / Eco) (Laser Phosphor Light Engine)	
Throw Ratio*	1.48 ~ 1.62	
Image Size (Diagonal)*	30" - 300"	
Projection Distance*	1.00 m - 10.00m (3.8ft to 32.8 ft)	
Projection Lens*	F = 2.5 – 2.67, f = 21.86 – 24.00mm	
Zoom Ratio*	1.1x	
Aspect Ratio	16:9	
Offset	116%±5% (Full Height)	
Keystone Correction	H/V ±30° (Auto V Keystone)	
Horizontal Frequency	15K~102KHz	
Vertical Scan Rate	24~120KHz	
3D Functionality	Yes (DLP® Link™, HDMI v1.4a Blu-ray, Top-Bottom / Frame-Sequential / Frame Packing / Side By Side)	
Speaker	15W (Mono)	
Computer Compatibility	VGA (640 x 480) to WUXGA (1920 x 1200-RB)	
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
I/O Connection Ports	HDMI v2.0 (x2) (HDCP v2.3 Compliant), Audio-Out (Mini-Jack)(x1), USB 1.1(5V/1.5A)(x1) , RS232(x1)	
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar	
Dimensions (WxDxH)	278 x 216 x 115.5mm (10.94" × 8.50" × 4.55")	
Weight	2.8 kg (6.17 lbs)	
Available Colors	White	
Noise Level	34dB/29dB (Normal/Eco Mode) ± 2dB	
Power Supply	AC 100-240V, 50/60Hz / DC 19.5V/9.23A 180W	
Power Consumption	Normal	182W (±15%)
	Eco	135W (±15%)
	Eco Standby	Less than 0.5W
Environmental Conditions	Operating	At temperature 0 to 40 °C±2 °C, relative humidity 10% to 80%,non-condensation
	Storage	At temperature -20 to 60°C, relative humidity 5% to 90%,non-condensation
Standard Accessories	AC Power Cord, 180W Adaptor, HDMI Cable, Remote Control, Documentation Kit, Lens Cap	
Optional Accessories	VWD-01 **	

Photos



* Note: Brightness specifications are compliance with ISO 21118 standards

**Note: VWD-01 is a wireless display dongle module.

© 2026 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.