



## High Brightness Short-Throw Projector

### FEATURES

- Bright 3,300 ANSI lumens with a high 15,000:1 contrast ratio
- XGA resolution with a maximum resolution up to WUXGA
- Delivers a 77" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows a presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



## Large Screen from Short distance

The DX881ST is designed to cater for the education needs. The DX881ST delivers a 77" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,300 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



## DX881ST SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	3300
	<b>Native Resolution</b>	XGA (1024x768)
	<b>Max. Supported Resolution</b>	WUXGA (1920x1200)@60Hz
	<b>Native Aspect Ratio</b>	4:3
	<b>Contrast Ratio</b>	15,000:1
	<b>Keystone Correction</b>	+/-40 Degree; +/- 40 Steps
Optical	<b>Throw Ratio</b>	0.62
	<b>Zoom Ratio</b>	Fixed
	<b>Lens Shift ( Based on Full Image Height)</b>	NA
	<b>Image Size (Diagonal)</b>	60" - 100"
	<b>Projection Distance</b>	763 - 1273 mm
	<b>Projection Lens</b>	F = 2.8. f = 7.26 mm
	<b>Offset (Based on Full Image Height)</b>	114%
Features	<b>Features</b>	3D Features, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), Keypad lock, Wall Color Correction, Instant On/Off
Compatibility	<b>Video</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,L)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (x2), HDMI 1.4b (x1), S-Video (x1), Composite Video (x1), Audio-In (Mini-Jack) (x3), VGA-Out (15pin D-Sub) (x1), Audio-Out (Mini-Jack) (x1), RJ45 (x1), IP Telnet Capable Over RJ-45, 12v Trigger (3.5mm JACK), RS-232 (x1), USB A (Yes, 5V Power), USB miniB (x1 Service), Microphone (Mini-Jack) (x1)
General	<b>Dimensions (W x D x H)</b>	314 x 216 x 126 mm
	<b>Weight</b>	3.2
	<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode)
	<b>Lamp Life and Type</b>	3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn. Eco)
	<b>Speakers</b>	10W x1
	<b>Noise Level</b>	36dB/32dB (Normal/Eco)
	<b>Standard Accessories</b>	VGA Cable, Component Cable, User Manual (CD), Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	<b>Optional Accessories</b>	Spare Lamp P/N (5811119560-SVV), Remote Control P/N (5041818400)
	<b>Warranty</b>	Standard Warranty: 3 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	<b>UPC Code</b>	814964 339836