



High Brightness Short-Throw Projector

FEATURES

- Short-Throw 0.52:1 T.R.
- High Brightness 3600 ANSI and 12000:1 High Contrast Ratio
- Delivers a 88" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



Large screen from short distance

The DW882ST is designed to cater for the education needs. The DW882ST delivers a 88" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,600 ANSI Lumens and contrast ratio of 15,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.



DW882ST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3600 ANSI Lumens
	Native Resolution	WXGA (1280 x 800)
	Max. Supported Resolution	WUXGA (1920x1200) @60Hz
	Native Aspect Ratio	16:10
	Contrast Ratio	15,000:1
	Keystone Correction	+/-40 Degree; +/- 40 Steps
	Optical	Throw Ratio
Zoom Ratio		Fixed
Lens Shift (Based on Full Image Height)		NA
Image Size (Diagonal)		70" - 100"
Projection Distance		779 - 1127 mm
Projection Lens		F = 2.8. f = 7.51 mm
Offset (Based on Full Image Height)		112%
Features		Features
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI 1.4b (x1), S-Video (x1), Composite Video (x1), Audio-In (Mini-Jack) (x3), VGA-Out (15pin D-Sub) (x1), Audio-Out (Mini-Jack) (x1), RJ45 (x1), IP Telnet Capable Over RJ-45, 12v Trigger (3.5mm JACK), RS-232 (x1), USB A (5V Power), USB miniB (x1 Service), Microphone (Mini-Jack) (x1)
General	Dimensions (W x D x H)	314 x 216 x 126 mm
	Weight	3.2 kg
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode)
	Lamp Life and Type	3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn.Eco)
	Speakers	10W x1
	Noise Level	36dB/32dB (Normal/Eco)
	Standard Accessories	VGA Cable, Component Cable, User Manual (CD), Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811119560-SVV), Remote Control P/N (5041818400)
	Warranty	Standard Warranty: 3 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	UPC Code	814964 339843