



WUXGA Large Venue Projector

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 6,200 ANSI lumens of brightness with single-lamp system
- WUXGA resolution for clear and crisp image
- HDBaseT for robustness with long signal transmission
- Installation flexibility is ensured with 5 optional lenses from 0.78:1 to 3.00-5.01:1 throw ratio range
- Wide lens shift range allows easy placement of the projector without distorting the image
- Image adjustment is made easy with 4 corner correction and keystone correction
- Easy projector monitor and control over network



High performance and easy installation features

The DU5671 offers a range of features that make it the ideal projector choice for the professional installation market. In addition to 6200 ANSI lumens of brightness, the WUXGA image resolution delivers excellent fidelity and large screen area for simultaneous display of video conferencing, presentations, and display of charts and graphs. With the installer in mind the DU5671 features horizontal and vertical lens shift as well as a centered lens for easy installation and maintenance. The projector has five interchangeable lens options for flexible positioning with regard to varying screen sizes or projection distance requirements and a comprehensive range of connectivity options.



DU5671

SPECIFICATIONS

| | | |
|---------------|---|--|
| Image | Display Type | Single chip DLP® Technology by Texas Instruments |
| | Brightness | 6200 ANSI Lumens |
| | Native Resolution | WUXGA (1920 x 1200) |
| | Max. Supported Resolution | WUXGA (1920 x 1200) @60Hz |
| | Native Aspect Ratio | 16:10 |
| | Contrast Ratio | 2,000:1 |
| | Keystone Correction | Vertical +/-30°; Horizontal +/-25° |
| Optical | Zoom Ratio | Depending on lens selection. Manual Zoom & Focus |
| | Lens Shift (Based on Full Image Height) | Vertical: +55%, -15%; Horizontal: +/-5% |
| | Image Size (Diagonal) | Depending on lens selection. See lens table below. |
| | Projection Distance | Depending on lens selection. See lens table below. |
| | Projection Lens | 5 optional lenses from 0.78:1 to 3.00-5.01:1 throw ratio range |
| | Offset (Based on Full Image Height) | Manual Lens Shift |
| Features | Features | 3D Mandatory Formats supported (top/bottom, right/left, frame sequential) |
| Compatibility | Video | SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L) |
| Connectivity | I/O Connection Ports | VGA-In (15pin D-Sub) (x2), HDMI v.1.4b (x2), DVI-D, Component (5 BNC) (RGBHV) , S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack) (x2), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45 (x2: HDBaseTx1, LANx1), 12v Trigger (3.5mm Mini-Jack), RS-232, 3D-Sync (Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote) |
| General | Dimensions (W x D x H) | 432 x 345 x 181mm |
| | Weight | 8.8 kg |
| | Power | Supply: AC 100-240V, 50/60Hz. Consumption: 410W (Eco Mode), 540W (Normal Mode), <0.5W (Standby) |
| | Lamp Life and Type | 1,500 / 2,000 Hours (Normal / Eco. Mode), 430W / 320W |
| | Speakers | 3W |
| | Noise Level | 43dB/38dB (Normal/Eco Mode) |
| | Standard Accessories | VGA Cable, User Manual (CD), Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord |
| | Optional Accessories | Spare Lamp P/N (5811122169-SVV), 3D Glasses P/N (3534257700), Remote Control P/N (5041846600) |
| | Warranty | Large Venue Warranty: 5 years projector / 1 year on lamp or 1.000 hours whichever comes first |
| | UPC Code | 813097023384 |

OPTIONAL LENSES

| Lens Name | Standard Lens | Wide Fix | Long Zoom 1 | Long Zoom 2 | Short Throw |
|----------------------------|---------------------------|----------------------------------|----------------------------------|---------------------------|---------------------------|
| Aspect Ratio | 16:10 | 16:10 | 16:10 | 16:10 | 16:10 |
| Throw Ratio | 1.54 - 1.93:1 | 0.78:1 | 1.93 - 2.89:1 | 3.00 - 5.01:1 | 1.1-1.3:1 |
| Projection Distance | 1.5m-7m | 0.5m-3m | 2m-20m | 3m-20m | 1m-9m |
| Image Size | 30-300 | 25-200 | 33-481 | 35-400 | 30-300 |
| Zoom | 1.25x | 1x | 1.5x | 1.67x | 1.18x |
| F Number | 2.46 - 2.56 | 2.5 | 2.5 - 3.1 | 2.2 - 2.5 | 2.05 - 2.27 |
| Focal Length | 22.8 - 28.5 mm | 11.46 mm | 28.5 - 42.75 mm | 44.5 - 74.19 mm | 16.64 - 19.54 mm |
| Part Number | 5811119236-SVV (LNS-5SZ1) | 5811120818-SVV (VL904G/LNS-5FX2) | 5811119237-SVV (VL908G/LNS-5LZ1) | 5811120055-SVV (LNS-5LZ2) | 5811120054-SVV (LNS-5STZ) |